



Fiber Tools & Accessories

ISO 9001 Certified

S918A Temporary Fiber Aligner



Description

The S918A creates a temporary connection of single to 12- ribbon fibers.

Specifications

Item	Description
Fiber Type	Silica glass-based optical fiber
Ribbon Count	2 - 12 Fiber Ribbon
Coating	250 m - 900 m Single Fiber 300 m - 400 m Ribbon Fiber (250 m pitch)
Cleave Length	10mm
Typical Loss*	0.2dB (using matching gel)
Pushing Mechanism	manual dial wheel
Light	switch turns light on in magnification area
Dimensions	body: 131W x 90D x 58H (mm) case: 385W x 270D x 95H (mm)
Weight	body: 540 (g) case: 1250 (g)

* Lab conditions

Standard Package

Item	P/N	QTY	Note
Main Body	S918A-01	1	
Light	S918A-02	1	
Matching Gel	S918X-31	1	10cc/50g
Bamboo Pick	S918X-32	5	
Case	S918X-33	1	
Manual	---	1	

S70X Fiber Holders



Description

All FITEL splicers have the option of using a fiber holder system for easy fiber preparation and splicing (required for S199M series)

Line-Up

P/N	Fiber Type	Applicable Machine
S706S-025	250 m single fiber	S199M12, S199M24, S918A
S706S-040	400 m single fiber	S199M12, S199M24, S918A
S706S-090	900 m single fiber	S199M12, S199M24, S918A
S706A-002	2-fiber ribbon	S199M12, S199M24, S918A
S7064-004	4-fiber ribbon	S199M12, S199M24, S918A
S701A-005	5-fiber ribbon	S199M12, S199M24, S918A
S706A-006	6-fiber ribbon	S199M12, S199M24, S918A
S706A-008	8-fiber ribbon	S199M12, S199M24, S918A
S706A-010	10-fiber ribbon	S199M12, S199M24, S918A
S706A-012	12-fiber ribbon	S199M12, S199M24, S918A
S706A-024	24-fiber ribbon	S199M24
S707S-250	250 m single fiber	S176CF, S176CR, S176LP
S707S-400	400 m single fiber	S176CF, S176CR, S176LP
S707S-900	900 m single fiber	S176CF, S176CR, S176LP
S709S-250	250 m single fiber	S121A, S121M
S709S-900	900 m single fiber	S121A, S121M
S709A-002	2-fiber ribbon	S121M
S709A-004	4-fiber ribbon	S121M
S710S-080	80 m single fiber	S183PM
S710S-250	250 m single fiber	S183PM
S710S-400	400 m single fiber	S183PM
S710S-900	900 m single fiber	S183PM

Application

